



November 25, 1992

Mary Beth Novy, RPM U.S. Environmental Protection Agency 77 West Jackson Blvd., HSRW-6J Chicago, IL 60604

RE: Albion-Sheridan Township Landfill (11-5LAN)

Dear Mary Beth:

Pursuant to the November 10, 1992 on-site meeting to finalize the selection of the remaining drilling locations, I am enclosing a table summarizing the proposed well locations and estimated screen intervals. Also enclosed is a location map showing the remaining proposed well locations.

WWES will not attempt to install MW-10 through MW-13 until we are notified by you that the access issues have been taken care of.

Also, please find enclosed the original signature page for the Albion-Sheridan Township Landfill Quality Assurance Project Plan.

Sincerely yours,

WW ENGINEERING & SCIENCE, INC.

**Environmental Services Division** 

Myaboth Mr. Whl

Elizabeth M. Uhl

Site Project Manager

cc: Gene Hall, MDNR

Rick Trippel, WWES

04011, 32

## **DESCRIPTION OF SCREENED INTERVAL**

WELL LOCATION	WELL	SCREENED INTERVAL(ft)	Section 1150 of Contesting 1000
MW-1 ,		32.5-37.5 54-59 67.5-72.5	Approximately 2 feet below the water table.  Opposite zone of high conductivity identified during geophysical logging. In shallow bedrock.
MW-2	SG* WB SB*	29-34 48-53 60-65	Approximately 2 feet below the water table.  Opposite zone of high conductivity identified in MWs-1, 3 & 4 during geophysical logging. In shallow bedrock.
мw-з	SG* WB* SBA*	37-42 54-59 64.5-69.5	Approximately 8 feet below the water table in zone of higher conductivity with freons.  Opposite zone of high conductivity identified during geophysical logging.  In shallow bedrock.
MW-4	SG WB* SB* DB*	31.5-36.5 56-61 68-73 95-100	Approximately 2 feet below water table and opposite zone of higher conductivity observed during geophysical logging.  Opposite zone of high conductivity identified during geophysical logging.  In shallow bedrock.  Approximately 20 feet below shallow bedrock well in which higher conductivity and low Eh were measured.
MW-5	SG*	23-28 70.5-75.5	Approximately 2 feet below the water table. In shallow bedrock.
MW-6	SG WB* SB*	23-28 46.5-51.5 70.5-75.5	Approximately 2 feet below the water table.  Opposite zone of higher conductivity observed during vertical sampling and zone of higher conductivity observed in MW-4. In shallow bedrock.
MW-7	SG WB SB	906 906	Approximately 2 feet below the water table.  Opposite zone of higher conductivity observed during vertical sampling and zone of higher conductivity observed in MW-4. In shallow bedrock.
MW-8	SG WB SB	31-36** 47-52** 59-64**	Approximately 2 feet below the water table.  Set in stratigraphic zone in which higher conductivity was identified in MWs-1,3 & 4 during geophysical logging. In shallow bedrock with top approximately 10-15 feet below depth of auger refusal.
MW-9	SG WB SB	12-17** 27-32** 39-44**	Approximately 2 feet below the water table.  Set in stratigraphic zone in which higher conductivity was identified in MWs-1,3 & 4 during geophysical logging.  In shallow bedrock with top approximately 10-15 feet below depth of auger refusal.
MW-10	SG	3-6**	Approximately 2 feet below the water table.
MW-11	SG	3-6**	Approximately 2 feet below the water table.
MW-12	SG	3-6**	Approximately 2 feet below the water table.
MW-13	SG	3-6**	Approximately 2 feet below the water table.
LF-2		23-28**	Screen straddling water table, downgradient (southwest) of partially buried drums (approx. N5950 E4760)
LF-3		25-35**	Boring in central portion of southern half of landfill. Screened only if water table lies above base of fill. (approx. N5500 E4600)

ALBWELL wk1

Well is installed.
 Screened intervals estimated based on existing shallow bedrock wells and/or estimated depth of water table, actual depths subject to change.
 Approval of well location by landowner pending, depth of screen can be estimated after location is selected.

